



Eclipse InTrack – The art of illuminating

One spotlight system and 28,000 possibilities: with interchangeable darklight lenses and ultra-slim adapters

In five sizes, Eclipse offers high-end technology, maximum visual comfort and a system scope for all applications – in museums and galleries, but also for exclusive retail projects. Interchangeable lens units define the light distributions – also as zoom spotlights and contour spotlights. With only one light point and an almost invisible beam path, the new Darklight lenses create a magical appearance. Refine with accessories: conversion

filters create additional spectra and tunable white and RGBW are available for dynamic scenes. Modern connectivity such as Multi Dim for DALI, Push Dim or wireless standards such as Casambi Bluetooth make Eclipse particularly smart.



Structure and characteristics

The features described here are typical of products in this range. Special versions may offer additional or varying features. A comprehensive description of the features of individual products can be found on our website.

1 ERCO lenses

- Made of optical polymer
- Darklight lenses: narrow spot, spot, flood, wide flood or extra wide flood
- Spherolit lenses: oval flood, oval wide flood or wallwash
- Zoom lenses: zoom spot or zoom oval; continuously focusable
- Projection lenses: narrow framing or wide framing; continuously focusable

2 Lens unit

- Rotatable through 360°
- Polymer, white or black
- Contour spotlights with framing attachment

3 ERCO LED-module

- High-power LEDs: warm white (2700K or 3000K), neutral white (3500K or 4000K), tunable white (2700-7500K) or RGBW
- Collimating lens made of optical polymer

4 Housing and bracket

- White (RAL9002), black or silver
- Die cast zinc or cast aluminium, powder-coated
- Pivotal 0°-270°
- Bracket: cast aluminium/polymer; rotatable through 360° on adapter

5 Control gear

- Switchable, On-board Dim, Multi Dim, Multi Dim+On-board Dim, Casambi Bluetooth or Zigbee
- Multi Dim version: DALI dimmable, Push Dim or dimming with external dimmers (leading edge-/trailing edge-/ universal dimmer) possible
- On-board Dim version: rotary control for control of brightness on the luminaire

6 ERCO Intrack adapter, 3-circuit adapter or DALI adapter

Variants on request

- Housing: 10,000 further colours
- Please contact your ERCO consultant.



Design and application:
www.erco.com/eclipse-intrack

Eclipse InTrack for track 220-240V



Darklight lens

The Darklight lens not only creates a magical impression with just one light point. It also features precise, uniform light distributions, wide flexibility in the selection of beam characteristics and state of the art efficiency.



Contour spotlights

Framing attachments enable a sharply defined light beam. In this way fascinating effects can be created with contour spotlights, where crisply illuminated pictures appear to illuminate from within.



Zoom spotlights

The light beam diameter can be infinitely adjusted from spot (15°) to wide flood (65°) by simply turning the lens. Zoom spotlights are particularly suitable for illuminating areas with changing exhibits and merchandise.



Coloured light

Using coloured light, the environment can be designed and transformed with either subtle or dramatic contrasts. LEDs enable you to generate coloured light very efficiently and flexibly.



Tunable white technology

Just as the colour temperature outdoors changes continuously during the day, the colour temperature of indirect lighting can be adjusted indoors to e.g. support lighting concepts for Human Centric Lighting.

Special characteristics



Efficient darklight technology



Contour spotlight



Zoom spotlight



Coloured light



Tunable white



ERCO high-power LEDs



Optical cut-off 40°/50°/60°



Different light distributions



Oval flood, freely rotatable



Different light colours



Excellent thermal management



EMC-optimised



Various housing colours



Various construction sizes



Pivotable through 270°



Accessory for maximum visual comfort



Switchable



On-board Dim



Multi Dim



Multi Dim + On-board Dim



Casambi Bluetooth




Zigbee

Eclipse InTrack for track 220-240V – Luminaire arrangement

Spotlights

Narrow spot, Spot, Flood




Accentuation

Works of art, merchandise and architectural details are effectively accentuated with Eclipse InTrack. The ideal angle of tilt (α) for this is around 30° . The object is modelled without distorting the effect as a result of excessive shadowing. It also prevents shadows cast by the observer.

Arrangement: $\alpha = 30^\circ$

Zoom spotlights

Zoom spot, Zoom oval




Accentuation

Zoom spotlights feature a continuously adjustable beam angle. With the spot to wide flood zoom range, smaller works of art can be accentuated effectively at an inclination angle (α) of approximately 30° . The oval zoom is suitable for linear works of art. The object is modelled without distorting the effect as a result of excessive shadowing. It also prevents shadows cast by the observer.

Arrangement: $\alpha = 30^\circ$


Contour spotlights

Narrow framing, Wide framing




Projection

Contour spotlights generate freely adjustable, crisp-edged light beams. As a result fascinating effects can be created where pictures appear to illuminate from within. Select narrow framing to accurately illuminate small exhibits from a long distance and wide framing to accurately illuminate large exhibits from a short distance.



Floodlights

Wide flood, Extra wide flood, Oval wide flood, Oval flood




Washlighting

The ideal angle of tilt (α) for floodlighting objects with a long, square shape, e.g. pictures, sculptures or merchandise displays, is around 30° .

Arrangement: $\alpha = 30^\circ$

Eclipse InTrack for track 220-240V – Luminaire arrangement


Lens wallwashers
Wallwash



Wallwashing

For uniform vertical lighting, the distance to the wall (a) of Eclipse InTrack lens wallwashers should be around one third of the room height (h). This results in an angle of tilt (a) of approx. 35°.

Arrangement: $a = 1/3 \times h$ or $\alpha = 35^\circ$




For good longitudinal uniformity, the spacing (d) of Eclipse InTrack lens wallwashers can be up to 1.2 times the distance to the wall (a).

Arrangement: $d \leq 1.2 \times a$


Optimal wall distances and luminaire spacing values for individual products are specified in the wall-washer tables at www.erco.com.

Eclipse InTrack for track 220-240V

Size



XS
Ø 32mm



S
Ø 60mm

LED module
Maximum value
at 4000K CRI 82

2W/272lm	3.1W/382lm (Narrow spot)
3.1W/382lm	

8.1W/1086lm	3.1W/382lm (Narrow spot)
12.4W/1528lm	

Light colour

	2700K CRI 92		3500K CRI 92
	3000K CRI 92		4000K CRI 82
	3000K CRI 97		4000K CRI 92

	2700K CRI 92		3500K CRI 92
	3000K CRI 92		4000K CRI 82
	3000K CRI 97		4000K CRI 92

Light distribution

Spotlights		Floodlights	
	Narrow spot		Wide flood
	Spot		Extra wide flood
	Flood		Oval flood
	Zoom spotlights		Oval wide flood
	Zoom spot	Lens wallwashers	
	Zoom oval		Wallwash

Spotlights		Floodlights	
	Narrow spot		Wide flood
	Spot		Extra wide flood
	Flood		Oval flood
	Zoom spotlights		Oval wide flood
	Zoom spot	Lens wallwashers	
	Zoom oval		Wallwash
Contour spotlights			
	Narrow framing		
	Wide framing		

Control

	Switchable		On-board Dim
	Multi Dim ✓ DALI dimmable ✓ Push Dim ✓ Phase dimmable		Multi Dim + On-board Dim ✓ DALI dimmable ✓ Push Dim ✓ Phase dimmable ✓ Dimmable via rotary control
	Casambi Bluetooth + DALI via Gateway		Zigbee

	Switchable		On-board Dim
	Multi Dim ✓ DALI dimmable ✓ Push Dim ✓ Phase dimmable		Multi Dim + On-board Dim ✓ DALI dimmable ✓ Push Dim ✓ Phase dimmable ✓ Dimmable via rotary control
	Casambi Bluetooth + DALI via Gateway		Zigbee

Colour (housing)

	White		Silver
	Black		10,000 colours *

	White		Silver
	Black		10,000 colours *

Accessory

	Lenses		Lens Units		Snoot		Add-on Control Units
	Filter		Honeycomb louvre		Barn doors		DALI Casambi Gateway

5.8W/698lm

Tunable white

Spotlights	Floodlights
Spot	Wide flood
Flood	Extra wide flood
Zoom spotlights	Oval flood
Zoom spot	Oval wide flood
Zoom oval	Lens wallwashers
Contour spotlights	Wallwash
Narrow framing	
Wide framing	

Multi Dim ✓ DALI dimmable ✓ Push Dim ✓ Phase dimmable	Multi Dim + On-board Dim ✓ DALI dimmable ✓ Push Dim ✓ Phase dimmable ✓ Dimmable via ✓ rotary control
Casambi Bluetooth + DALI via Gateway	Zigbee

White	Silver
Black	10,000 colours *

9.3W/800lm

RGBW

Spotlights	Floodlights
Spot	Wide flood
Flood	Extra wide flood
Zoom spotlights	Oval flood
Zoom spot	Oval wide flood
Zoom oval	Lens wallwashers
Contour spotlights	Wallwash
Narrow framing	
Wide framing	

Multi Dim ✓ DALI dimmable ✓ Push Dim ✓ Phase dimmable	Multi Dim + On-board Dim ✓ DALI dimmable ✓ Push Dim ✓ Phase dimmable ✓ Dimmable via ✓ rotary control
Casambi Bluetooth + DALI via Gateway	Zigbee

White	Silver
Black	10,000 colours *

* available on request


Article numbers and planning data:
www.erco.com/018437

Design and application:
www.erco.com/eclipse-intrack



Eclipse InTrack for track 220-240V

Size



M
Ø 92mm

LED module Maximum value at 4000K CRI 82

14.1W/1901lm	4.2W/481lm (Narrow spot)
21.6W/2673lm	

18.2W/2156lm

Light colour

	2700K CRI 92		3500K CRI 92
	3000K CRI 92		4000K CRI 82
	3000K CRI 97		4000K CRI 92

	Tunable white
--	---------------

Light distribution

Spotlights	Floodlights
Narrow spot	Wide flood
Spot	Extra wide flood
Flood	Oval flood
Zoom spotlights	Oval wide flood
Zoom spot	Lens wallwashers
Zoom oval	Wallwash
Contour spotlights	
Narrow framing	
Wide framing	

Spotlights	Floodlights
Spot	Wide flood
Flood	Extra wide flood
Zoom spotlights	Oval flood
Zoom spot	Oval wide flood
Zoom oval	Lens wallwashers
Contour spotlights	Wallwash
Narrow framing	
Wide framing	

Control

Switchable	On-board Dim
MULTI Multi Dim ✓ DALI dimmable ✓ Push Dim ✓ Phase dimmable	MULTI+ Multi Dim + On-board Dim ✓ DALI dimmable ✓ Push Dim ✓ Phase dimmable ✓ Dimmable via rotary control
Casambi Bluetooth + DALI via Gateway	Zigbee

MULTI Multi Dim ✓ DALI dimmable ✓ Push Dim ✓ Phase dimmable	MULTI+ Multi Dim + On-board Dim ✓ DALI dimmable ✓ Push Dim ✓ Phase dimmable ✓ Dimmable via rotary control
Casambi Bluetooth + DALI via Gateway	Zigbee

Colour (housing)

White	Silver
Black	10,000 colours *












White	Silver
Black	10,000 colours *





Accessory





Lenses	Lens Units	Snoot	Add-on Control Units
Filter	Honeycomb louvre	Barn doors	DALI Casambi Gateway

17.9W/1516lm

 RGBW

Spotlights	Floodlights
 Spot	 Wide flood
 Flood	 Extra wide flood
Zoom spotlights	 Oval flood
 Zoom spot	 Oval wide flood
 Zoom oval	Lens wallwashers
Contour spotlights	 Wallwash
 Narrow framing	
 Wide framing	

 Multi Dim ✓ DALI dimmable ✓ Push Dim ✓ Phase dimmable	 Multi Dim + On-board Dim ✓ DALI dimmable ✓ Push Dim ✓ Phase dimmable ✓ Dimmable via ✓ rotary control
 Casambi Bluetooth + DALI via Gateway	 Zigbee

 White	 Silver
 Black	 10,000 colours *

* available on request


Article numbers and planning data:
www.erco.com/018437

Design and application:
www.erco.com/eclipse-intrack



Eclipse InTrack for track 220-240V

Size



L
Ø 129mm

LED module Maximum value at 4000K CRI 82

19.9W/2834lm	12.6W/1443lm (Narrow spot)
30.3W/4035lm	

36.7W/3346lm

Light colour

	2700K CRI 92		3500K CRI 92
	3000K CRI 92		4000K CRI 82
	3000K CRI 97		4000K CRI 92

	Tunable white
--	---------------

Light distribution

Spotlights	Floodlights
Narrow spot	Wide flood
Spot	Extra wide flood
Flood	Oval flood
Zoom spotlights	Oval wide flood
Zoom spot	Lens wallwashers
Zoom oval	Wallwash
Contour spotlights	
Narrow framing	
Wide framing	

Spotlights	Floodlights
Spot	Wide flood
Flood	Extra wide flood
Zoom spotlights	Oval flood
Zoom spot	Oval wide flood
Zoom oval	Lens wallwashers
Contour spotlights	Wallwash
Narrow framing	
Wide framing	

Control

Switchable	On-board Dim
Casambi Bluetooth	Zigbee
DALI	

Casambi Bluetooth	Zigbee
DALI	

Colour (housing)

White	Silver
Black	10,000 colours *












White	Silver
Black	10,000 colours *




Accessory





Lenses	Lens Units	Snoot	DALI Casambi Gateway
Filter	Honeycomb louvre	Barn doors	

36W/2534lm

 RGBW

Spotlights	Floodlights
 Spot	 Wide flood
 Flood	 Extra wide flood
Zoom spotlights	 Oval flood
 Zoom spot	 Oval wide flood
 Zoom oval	Lens wallwashers
Contour spotlights	 Wallwash
 Narrow framing	
 Wide framing	

 Casambi Bluetooth	 Zigbee
 DALI	

 White	 Silver
 Black	 10,000 colours *

* available on request


Article numbers and planning data:
www.erco.com/018437

Design and application:
www.erco.com/eclipse-intrack



Eclipse InTrack for track 220-240V

Size



XL
 Ø 153mm

LED module

Maximum value at 4000K CRI 82

32.9W/4624lm	16.8W/1924lm (Narrow spot)
51.9W/6731lm	

Light colour

	2700K CRI 92		3500K CRI 92
	3000K CRI 92		4000K CRI 82
	3000K CRI 97		4000K CRI 92

Light distribution

Spotlights	Floodlights
Narrow spot	Wide flood
Spot	Extra wide flood
Flood	Oval flood
Lens wallwashers	Oval wide flood
Wallwash	

Control

Switchable	DALI
Casambi Bluetooth	Zigbee

Colour (housing)

	White		Silver
	Black		10,000 colours *

Accessory

	Lenses		Lens Units		Snoot		DALI Casambi Gateway
	Filter		Honeycomb louvre		Barn doors		

* available on request

Article numbers and planning data:
www.erco.com/018437

Design and application:
www.erco.com/eclipse-intrack



