




## Compar linear – Powerhouse for linear aesthetics

### **Differentiated light from the ceiling in an innovative design**

The recessed downlights with a concise and linear housing shape, available from widths of 52mm, set accents in the ceiling design and simultaneously function as highly efficient lighting tools with high levels of visual comfort. The wide spectrum of distribution options for nuanced general and office lighting convinces in any high-quality architecture. Compar is an attractive alternative to lighting with conventional linear luminaires. With Compar, ceiling-integrated lighting concepts can be realised

in restaurants as well as administrative, cultural and office buildings. Tunable white enables flexible control of colour temperature – ideal for Human Centric Lighting in modern work and cultural spaces.

## Compar linear Recessed luminaires



### Structure and characteristics

The features described here are typical of products in this range. Special versions may offer additional or varying features. A comprehensive description of the features of individual products can be found on our website.

#### 1 ERCO lens system

- Made of optical polymer
- Light distributions: spot, flood, wide flood, extra wide flood, oval wide flood or oval flood

or

#### Reflector (lens wallwasher)

- Polymer, silver vaporised, mirror-finish
- Softec lens

#### 2 ERCO LED-module

- High-power LEDs or Chip-on-board LEDs: warm white (2700K or 3000K), neutral white (3500K or 4000K) or tunable white (2700-6500K)

#### 3 Louvre

- Polymer, black lacquered or aluminium vaporised, silver, mirror-finish
- Downlight: cut-off angle 30°
- Wallwasher: cut-off angle 70°

#### 4 Mounting frame

- Covered mounting detail
- Mounting for ceiling thicknesses to max. 40mm
- Polymer, white
- For flush mounting: mounting frame to be ordered separately, fixing for ceiling thicknesses of 12.5-25mm

#### 5 Housing

- Aluminium profile, designed as heat sink

#### 6 Control gear

- Switchable, phase dimmable, DALI dimmable or Casambi Bluetooth
- Phase dimmable version: Dimming with external dimmers possible (trailing edge)


#### Variants on request

- Anti-dazzle louvre: coated matt gold, matt silver or matt champagne
  - Connection: 3- or 5-pole plug with connection cable (Wago or Wieland)
  - Mounting frame: 10,000 further colours
- Please contact your ERCO consultant.



Design and application:  
[www.erco.com/compar-linear](http://www.erco.com/compar-linear)

# Compar linear Recessed luminaires



## Louvres for efficient visual comfort

A louvre is designed to restrict the view into the luminaire, achieving efficient visual comfort with an emission angle of 90°. An anti-glare louvre available in black or silver enables the luminaire to blend with the material and colour of the ceiling.




## Tunable white technology

Just as the colour temperature outdoors changes continuously during the day, the colour temperature of indirect lighting can be adjusted indoors to e.g. support lighting concepts for Human Centric Lighting.



## Suitable for office workstations

ERCO develops luminaires with the specifications of good glare control and high visual comfort. UGR values are used as support for purely norm-referenced lighting. With downlights though this should not be carried out using 'blanket' values, but should be implemented according to the individual arrangement of luminaires in the room.



## Particularly efficient: up to 156lm/W

Reduce energy consumption, increase efficiency: Compar is the ideal solution for linear lighting concepts in offices, educational establishments and public buildings with special design requirements.



## Covered or flush mounting detail

Compar recessed downlights are supplied with an overlapping mounting detail. Flush mounting details are available as accessories to facilitate site logistics.

### Special characteristics



Excellent visual comfort



Tunable white



Suitable for office workstations



>130lm/W



Flush or covered mounting detail



ERCO High-power LEDs / ERCO Chip-on-Board LEDs



Efficient lens system



Cut-off 30°/70°



Different light colours



Excellent thermal management



EMC-optimised



Various construction sizes



Shallow recess depth



Tool-free mounting



Switchable



Phase dimmable



DALI dimmable




Casambi Bluetooth

## Compar linear Recessed luminaires – Luminaire arrangement


### Downlights

Spot, Flood, Wide flood, Extra wide flood



For optimum general lighting, the luminaire spacing ( $d$ ) between two Compar downlights may, as a rough guide, be up to 1.5 times the height ( $h$ ) of the luminaire above the working plane.

Arrangement:  $d \leq 1.5 \times h$




The wall offset should be half the luminaire spacing.

Arrangement:  $a = d / 2$

### Downlights oval wide flood

Oval wide flood




For efficient workplace illumination in the office, with optimal uniformity and good facial recognition, the luminaire spacing ( $d$ ) of Compar downlights with oval wide flood distribution ( $d$ ) may be up to 1.5 times the height ( $h$ ) of the luminaire above the working plane.

Arrangement:  $d \leq 1.5 \times h$

### Downlights oval flood


Oval flood



As a rough guide for uniform illumination, the luminaire spacing ( $d$ ) between two Compar downlights installed in a row may be up to 1.5 times the height ( $h$ ) of the luminaire above the working plane.


Arrangement:  $d \leq 1.5 \times h$

Application area: Hallways and corridors as well as above tables.




## Compar linear Recessed luminaires – Luminaire arrangement

Lens wallwashers  
Wallwash



For uniform vertical illuminance, the distance (a) of Compar lens wallwashers from the wall should be around one third of the wall height (h).

Arrangement:  $a = 1/3 \times h$



For good longitudinal uniformity, the spacing (d) of Compar lens wallwashers may be up to 1.3 times the offset from the wall (a).

Arrangement:  $d \leq 1.3 \times a$


Optimal wall offset and luminaire spacing values are indicated in the wallwasher tables on the product data sheets.

175 Eagle Street,  
Brisbane. Archi-  
tecture: Cox  
Architecture,  
Brisbane. Light-  
ing design: Cox  
Architecture,  
Brisbane. Photo-  
graphy: Jackie  
Chan, Sydney.




# Compar linear Recessed luminaires

Construction size



120mm



210mm

LED module  
Maximum value  
at 4000K CRI 92

6.1W/862lm
9.3W/1213lm

12.1W/1723lm
18.6W/2426lm

Light colour

	2700K CRI 92		3500K CRI 92
	3000K CRI 92		4000K CRI 92
	3000K CRI 97		

	2700K CRI 92		3500K CRI 92
	3000K CRI 92		4000K CRI 92
	3000K CRI 97		

Light distribution

Downlights	Downlights oval wide flood
Spot	Oval wide flood
Flood	Downlights oval flood
Wide flood	Oval flood
Extra wide flood	Lens wallwashers
	Wallwash

Downlights	Downlights oval wide flood
Spot	Oval wide flood
Flood	Downlights oval flood
Wide flood	Oval flood
Extra wide flood	Lens wallwashers
	Wallwash

Control

	Switchable		DALI
	Phase dimmable		Casambi Bluetooth

	Switchable		DALI
	Phase dimmable		Casambi Bluetooth

Colour (louvre)

	Silver
	Black

	Silver
	Black

Accessories

	Mounting frame		Suspension for control gear
	Mounting frame for ceiling channels		

12.1W/1228lm

 Tunable white

Downlights	Downlights oval wide flood
 Spot	 Oval wide flood
 Flood	Downlights oval flood
 Wide flood	 Oval flood
 Extra wide flood	Lens wallwashers
	 Wallwash

 DALI

 Casambi Bluetooth

 Silver

 Black



\* available on request

[www.erco.com/compar-linear](http://www.erco.com/compar-linear)



# Compar linear Recessed luminaires

Construction size



LED module  
Maximum value  
at 4000K CRI 92

24.3W/3446lm
37.3W/4853lm

48.5W/6893lm
74.6W/9706lm

Light colour

	2700K CRI 92		3500K CRI 92
	3000K CRI 92		4000K CRI 92
	3000K CRI 97		

	2700K CRI 92		3500K CRI 92
	3000K CRI 92		4000K CRI 92
	3000K CRI 97		

Light distribution

Downlights	Downlights oval wide flood
Spot	Oval wide flood
Flood	Downlights oval flood
Wide flood	Oval flood
Extra wide flood	Lens wallwashers
	Wallwash

Downlights	Downlights oval flood
Spot	Oval flood
Flood	Downlights oval wide flood
Wide flood	Oval wide flood
Extra wide flood	

Control

	Switchable		DALI
	Phase dimmable		Casambi Bluetooth

	Switchable		DALI
	Phase dimmable		

Colour (louvre)

	Silver
	Black

	Silver
	Black


Accessories

	Mounting frame		Suspension for control gear
	Mounting frame for ceiling channels		

\* available on request

[www.erco.com/compar-linear](http://www.erco.com/compar-linear)





Mercedes  
Ghistelinck,  
Kortrijk. Architec-  
ture: Goedefroo &  
Goedefroo, Wiels-  
beke. Lighting  
design: Vensol  
/ Goedefroo &  
Goedefroo. Pho-  
tography: Thomas  
Mayer, Neuss.

Arup, Sydney.  
Lighting design:  
Arup. Photography: Jackie Chan,  
Sydney.





Faerber Architekten,  
Mainz.  
Architecture: Faerber  
Architekten  
GbR, Mainz. Photography:  
Lukas Palik, Düsseldorf.